

LOW TORQUE PLUG VALVE LUBRICANT

Low Torque Plug Valve Lubricant was specially design for TE and LT Manifold Plug Valves. **Low Torque Plug Valve Lubricant** prevents unwanted material from scraping and grinding the plug valve sealing surfaces and delivers a true 100% bubble tight seal. **Low Torque Plug Valve Lubricant** is made from 100% synthetic materials and has a special additive which significantly reduces the operation torque on a TE and LT manifold plug valves. Regular greasing with **Low Torque Plug Valve Lubricant** will increase the service life of the internal parts of the valve. **Low Torque Plug Valve Lubricant** is resistant to natural gas, crude oil, organic acids, water, gasoline, jet fuel, lubricating oils, condensates, water, hydrocarbon gasses and is inhibited for use in H2S and CO2. **Low Torque Plug Valve Lubricant** is equivalent to the costly products on the market today.

Properties:

- Consistency, Cone Penetration (D-217) 250 to 265
- 100% synthetic
- Temperature range: 0 to 400°F
- Corrosion Inhibitor - Imidazoline Derivative
- Color: Black

Low Torque Plug Valve Lubricant is available in:

- LT-K - 12 ea "K" Sticks to a box
- LT-J - 16 ea "J" Sticks to a box
- LT-V4 - 4 ea 5lb "V" Sticks to a box
- LT-CT - 10 ea Cartridge per box
- LT-10 - 10lb Pails
- LT-5G - 5 Gallon Pail
- LT-16G - 16 Gallon Drum



CSN Solutions, Inc.
11311 Jones Rd W, Suite J
Houston, TX 77065
www.csn-inc.net



Ph/Text: 713-703-8561

Fax: 281-469-4298

Email: Chad@csn-inc.net