

Air Operated Grease Pumps



Part # 100-16G

100:1 Air Operated, 16 Gallon Grease Pump with the Following Features:

1. Air Inlet Shut On/Off Valve
2. Follower Plate and Spring
3. 20ft High Pressure Hose
4. Z-Swivel – Maneuver 360 degrees
5. Needle Valve – Controls Grease Flow
6. Tee with Gauge and Cover
7. 18" High Pressure Hose
8. Release Valve- Close valve to remove Coupler
9. Giant Button Coupler or Screw On Coupler –Your Choice



Part # 100-16G-D (Heavy Duty Dolly)

100:1 Air Operated, 16 Gallon Grease Pump with the Following Features:

1. Air Inlet Shut On/Off Valve
2. Follower Plate and Spring
3. 20ft High Pressure Hose
4. Z-Swivel – Maneuver 360 degrees
5. Needle Valve – Controls Grease Flow
6. Tee with Gauge and Cover
7. 18" High Pressure Hose
8. Release Valve- Close valve to remove Coupler
9. Giant Button Coupler or Screw On Coupler

CSN Solutions, Inc.
11311 Jones Rd. W, Suite J
Houston, TX 77065
www.csn-inc.net



Ph/Text: 713-703-8561

Fax: 281-469-4298

Email: Chad@csn-inc.net

Air Operated Grease Pumps



Part # 100-5G

100:1 Air Operated, 5 Gallon Grease Pump with the following features:

1. Air Inlet Shut On/Off Valve
2. Follower Plate and Spring
3. 20ft High Pressure Hose
4. Z-Swivel – Maneuver 360 degrees
5. Needle Valve – Controls Grease Flow
6. Tee with Gauge and Cover
7. 18" High Pressure Hose
8. Release Valve- Close valve to remove Coupler
9. Giant Button Coupler or Screw On Coupler –Your Choice



Part # 100-5G-D (Heavy Duty Dolly)

100:1 Air Operated, 5 Gallon Grease Pump with the following features:

1. Air Inlet Shut On/Off Valve
2. Follower Plate and Spring
3. 20ft High Pressure Hose
4. Z-Swivel – Maneuver 360 degrees
5. Needle Valve – Controls Grease Flow
6. Tee with Gauge and Cover
7. 18" High Pressure Hose
8. Release Valve- Close valve to remove Coupler
9. Giant Button Coupler or Screw On Coupler

CSN Solutions, Inc.
11311 Jones Rd. W, Suite J
Houston, TX 77065
www.csn-inc.net



Ph/Text: 713-703-8561

Fax: 281-469-4298

Email: Chad@csn-inc.net

10lb Pail Grease Guns



Activ-8 Part# A8-GUNC

The Activ-8 Sealant Injection Gun allows the user to load 2 ounces of product into the guns barrel with every stroke of the Jack Handle. The Activ-8 is capable of generating 10,000 psi and powered by an Air/Hydraulic Pump. Standard models come with a 10ft Hose Assembly but you can also get a 15ft, 20ft, 25ft and 30ft.



Hypregun Part # HGP-GUNC

The Hypregun Plus will generate 10,000 psi with only a 100 psi of air pressure. Simply attach the air supply, open the throttle valve and screw in the Valve Screw clockwise to create pressure and counterclockwise to release pressure. The Hypregun Plus is equipped with pneumatic wheels and a 10ft Hose Assembly. It's hard to determine how much grease is being injected into a valve on the Hypregun Plus but this would be a great chance to add a Digital Flow Meter.

Grease Pump Accessories



DFM-2

Add a Digital Flow Meter to your unit to determine how much grease is being injected in each valve.
¼" NPT Female Ports



HR-50FT-ASSY

Our 50ft Hose Reel Assembly come with a High Pressure Hose Reel, 50ft of High Pressure Hose, a Hose Stop, Jumper Hose and Flow Control Hose Assembly.

Rated to 10,000 psi



MAFRL-2

A Mini ¼" Air Filter/Regulator /Lubricator allow you to remove moisture from the system, regulate air pressure and lubricate the components inside the Air Motor.

Give us a call if you have a question.

CSN Solutions, Inc.
11311 Jones Rd. W, Suite J
Houston, TX 77065
www.csn-inc.net



Ph/Text: 713-703-8561

Fax: 281-469-4298

Email: Chad@csn-inc.net